

HiSeaVis All-in-One LED Display

AT135 Product Specification V1.0

Set Parameters	Screen size (diagonal)	135 inch
	Aspect ratio	16:9
	Pixel pitch	1.5625mm
	Resolution	1920*1080
	LED package	COB
	Screen size (W*H*D)	3000*1687.5*31mm
	Set size (W*H*D)	3025*1825*45 (59.5) mm
	Weight	115KG (without mobile stand and wall mount frame)
	Panel Maintenance	Front
	Installation	Mobile/Wall mounting
Optoelectronic Parameters	Brightness	600nits
	Refresh rate	3840Hz
	Gray scale	18bit
	Contrast	20000:1
	Color temperature	6500K-12000K
	Viewing angle	160° H/160° V
	LED lifetime	100000 Hours
Android System	OS	Android13.0
	CPU	Cortex A73*4+A53*4
	RAM	8GB
	Storage Memory	128GB
	Audio	2*18W speakers
OPS (optional)	SSD	256GB
	RAM	8GB
	CPU	Inter(R)Core(TM)i7-8550U
	OS	-
I/O	Front Connectors	USB3.0*2
	Bottom Connectors	HDMI IN*2 / RJ45*2 / 3.5mmHeadphone Jacket*1 / SPDIF / USB3.0*3 / USB2.0*2 / USB3.0 "D" / HDMI Out
	Buttons	VOL+ / VOL- / SOURCE / POWER
Power	Power supply	100~240VAC, 50/60Hz
	Average Power consumption	620W
	Max. Power consumption	1850W
Application Parameters	Operation temperature	-10°C-50°C
	Operation humidity	10%-80%RH No condensation
	Certification	CCC / CE / RoHS / FCC / ETL / UL

Note: Power consumption may vary within $\pm 15\%$, depending on the LED brightness of different batches. Actual values shall prevail.