

|                          |                               |                                                             |
|--------------------------|-------------------------------|-------------------------------------------------------------|
| Physical Parameters      | Pixel Configuration           | 1R1G1B                                                      |
|                          | LED Type                      | SMD2020                                                     |
|                          | Pixel Pitch                   | 2.5mm                                                       |
|                          | Module Size                   | 320×160mm                                                   |
|                          | Module Resolution             | 128×64 dots                                                 |
|                          | Display Area Size             | 1280×1920mm                                                 |
|                          | Screen Resolution             | 393216 dots/unit                                            |
|                          | Unit Size                     | W1280×H1930×D55mm                                           |
|                          | Flatness                      | Adjacent pixel gap ≤0.5mm; module seam ≤0.5mm               |
|                          | Unit Weight                   | 33 kg/unit                                                  |
|                          | Base Weight                   | 12 kg                                                       |
| Electronic Parameters    | Driving Type                  | 1/64 scan                                                   |
|                          | Control Mode                  | Synchronous / Asynchronous                                  |
|                          | Content Publishing            | WiFi / 4G / USB                                             |
| Optical Parameters       | Max Brightness                | 500 cd/m <sup>2</sup>                                       |
|                          | Horizontal Viewing Angle      | ≥140°                                                       |
|                          | Vertical Viewing Angle        | ≥110°                                                       |
| Electrical Parameters    | Input Voltage                 | AC 110V / 220V±15%                                          |
|                          | Power Supply                  | 5V/60A                                                      |
|                          | Power Consumption (Max / Avg) | approx. 500 W/m <sup>2</sup> / approx. 150 W/m <sup>2</sup> |
| Environmental Parameters | Operating Temperature         | -20°C~+60°C                                                 |
|                          | Operating Humidity            | 10%~65%RH                                                   |
| Installation             | Certification                 | CCC / CE / RoHS / FCC / ETL / UL                            |

Note: Specifications are subject to change due to product upgrades; the actual product shall prevail.