

HiSeaVis Rental LED Display

SVW3.9 Product Specification V1.0

Physical Parameters	Type	SMD1919
	Pixel Pitch	3.91
	Cabinet size (W x H x T)	W500xH1000xD78mm/W500xH500xD78mm
	Cabinet Resolutions (W x H)	128pixels x 256pixels/128pixels x 128pixels
	Weight	6.5kg±0.5/13 kg±0.5
	Cabinet material	Die-cast aluminum
	Size of module (W x H)	W250mmxH250mmxD15.5mm
	Connection method	Soft connection
Optoelectronic Parameters	Brightness (nits)	4500 nit
	Refresh rate	7680 Hz
	Gray scale	14 bits
	Max contrast	4000:1
	Color temperature	3000K-10000K (adjustable)
	Viewing angle (H / V)	H160°/V140°
	Type of driver	Constant Current, 1/16 Scanning
	Working voltage	AC100~240V (+/-10%) (50~60Hz)
	Power (Peak / Average) (W/m ²)	<800W/m ² / <300W/m ²
Application Parameters	Storage temperature / humidity	-40°C~+60°C/10%~85%RH
	Operating temperature / humidity	-20°C~+50°C/10%~80%RH
	Protection Grade	Front IP65/Rear IP54
	Cabinet maintenance mode	Rear Maintenance
	Certification	CCC / CE / RoHS / FCC / ETL / UL

Note: Power consumption may vary within ±15%, depending on the LED brightness of different batches. Actual values shall prevail.