

Physical Parameters	Model	Transparent LED Kiosk
	LED Specification	2121
	Pixel Pitch (mm) (horizontal/vertical)	3.91-3.91
	Pixel Density (dot/m ²)	65536
	Transparency Rate	95%
	Module Dimension (mm) (w*h)	250x2000
	Module Resolution (dot) (w*h)	64x504
	Profile Dimension (mm)(w*h)	1000x2288x550
	Overall Resolution (dot) (w*h)	256x504
	Weight (Kg/set)	83
Optoelectronic Parameters	Viewing Angle	Horizontal: 140°, Vertical: 140°
	Brightness(cd/m ²)	≥1700(Black Light) ≥3000(White Light)
	Maximum Power Consumption (W/m ²)	692(Black Light) 800(White Light)
	Average Power Consumption (W/m ²)	332(Black Light) 320(White Light)
	Color Temperature (K)	3000~10000
	Scanning Mode	Light & Driver Integrated, Static Driving
	Frame Rate (Hz)	60~120
	Lifespan	≥ 100,000.00 hours
	Gray Scale	16bit
	Input Voltage	AC100~240V 50/60Hz
Application Parameters	Working Voltage for Module	DC4.2V ±0.2V
	Working Temperature	Temperature -20°C ~50°C
	Working Humidity	Humidity 20%RH ~ 85%RH (Without Condensation)
	Storage Temperature	Temperature -20°C ~60°C
	Storage Humidity	Humidity 10%RH ~ 85%RH (Without Condensation)
	Protection Degree	IP20
	Installation Method	Floor Standing
	Installation Environment	Indoor
	Certification	CCC / CE / RoHS / FCC / ETL / UL

Note: Power consumption may vary within ±15%, depending on the LED brightness of different batches. Actual values shall prevail.